

SOCKET DUAL



Emmerich's Socket Dual series featuring Off-line technology UPS System, which provide reliable power protection for home appliances and computer. It provides battery backup and only surge-protected sockets to meet demand for multiple device.

To have surge protection for your home theater, Socket Dual is allowed to add coax surge protection. Socket Dual provides 6 output sockets with sufficient capacity for the central unit and Its compact size and versatility - push-button operation, LED/LCD status panel and user-replaceable batteries make Socket Dual easy to use to protect systems from surges and blackouts.

PERFORMANCES

- 350 VA / 400 VA / 550 VA / 600 VA / 750 VA / 800 VA Standby UPS.
- Compact size for standalone and mounting flexibility.
- Excellent microprocessor control guarantees high reliability.
- Auto restart while AC is recovering.
- Simulated sine wave output.
- Cold start function.
- Optional USB communication port.
- Optional 5V USB charger.
- Optional RJ11 and coax surge protection.
- Optional LCD version is also available upon request.

MODEL	SCD 350	SCD 550	SCD 750	SCD 400	SCD 600	SCD 800
CAPACITY	350 VA / 210 W	550 VA / 330 W	750 VA / 450 W	400 VA / 240 W	600 VA / 360 W	800 VA / 480 W
INPUT						
Voltage	110/120 VAC			220/230/240 VAC		
Acceptable Voltage Range	90 - 145 VAC			180 - 270 VAC		
Frequency Range	60 Hz / 50 Hz (Auto sensing)					
OUTPUT						
Voltage	110/120 VAC			220/230/240 VAC		
AC Voltage Regulation (Batt. Mode)	± 10 %					
Frequency Range (Batt. Mode)	60 Hz or 50 Hz ±1 Hz					
Transfer Time	Typical 2-6 ms, Max. 10ms					
Waveform (Batt. Mode)	Simulated Sinewave					
BATTERY						
Battery Type	12V/4Ah x 1	12V/4.5Ah x 1	12V/5Ah x 1	12V/4Ah x 1	12V/4.5Ah x 1	12V/5Ah x 1
Typical Recharge Time	8 hours recover to 90% capacity					
INDICATORS						
AC Mode	Green lighting					
Battery Mode	Yellow flashing					
Fault	Red lighting					
ALARM						
Battery Mode	Sounding every 10 seconds					
Low Battery	Sounding every second					
Overload	Sounding every 0.5 second					
Fault	Continuously sounding					
PROTECTION						
Full Protection	Overload, discharge, and overcharge protection					
PHYSICAL						
Dimension, D x W x H(mm)	305 x 158.5 x 95					
Net Weight (kgs)	2.5	2.6	2.9	2.5	2.6	2.9
ENVIRONMENT						
Humidity	0-90 % RH @ 0- 40°C (Non-condensing)					
Noise Level	Less than 40dB					

Product design, colour and specifications are subject to change without further notice.



PT. SENTRA POWER NUSANTARA

Office : Perkantoran Green Ville Blok AW No.20 Jakarta Barat - 11510, Indonesia
 Telp : +62 21 5698 1101 (Hunting)
 Fax : +62 21 5698 1102
 Email : info@sentrampower.com

